



# auxoMEDICAL

## Steris 3000 Series Medium Sterilizer - Refurbished *Models 3033, 3043, and 3053*

The Eagle 3000 series sterilizers can be used in a surgery center, hospital and laboratories:

**Prevaccum:** Ideal for quick and dependable sterilization. May be used on heat and moisture sensitive items. Prevaccum cycles include prevaccum, gravity, flash, express, leak test, daily air removal test and custom programmable cycles.

**Features:** Our Refurbished Steris Eagle Series sterilizers are equipped with Stage 3 Controls, impact printer, hinged front cabinet panel, resistance temperature detectors, automatic utilities startup/shutdown, steam bleed, steam purge, internal battery back-up for cycle memory, and pressure relief valve. Available in single and double door, pass-through options and right or left door swing.

**Free Standing or Recessed:** Choose to have your sterilizer recessed within a wall or free standing with durable high grade stainless steel side panels.

### Chamber Options:

Model 3033: Vacamatic, 26 x 37.5 x 36"

Model 3043: Vacamatic, 26 x 37.5 x 48"

Model 3053: Vacamatic, 26 x 37.5 x 60"

**Accessories** - Auxo Medical offers a variety of accessories to accompany your refurbished Steris sterilizer.

- Loading rack and two shelves for increased sterilization space and ease of use
- Cart and carriage makes transfer of items from an OR suite or other location to your sterilizer a breeze.
- Stainless steel cabinet package for free standing capability.
- Drain Cooler and water saver- reduce your water consumption and increase the life of your sterilizer and boiler with this simple addition.
- Steam generator in various sizes with auto blow-down options and water treatment



### Why an Auxo Medical refurbished Sterilizer?

Auxo Sterilizers are refurbished to the highest standards in the industry. We completely disassemble each sterilizer to its core, and completely rework or replace all parts and return the sterilizer to OEM standards. We do not substitute cheaper non-OEM parts like many of our competitors. Each sterilizer is reassembled, tested and is warranted against defects.



## Utility Requirements

---

All utility supplies should have manual shutoffs located where the sterilizer connects to the utilities. Any utilities supplied above the sterilizer should be directed downward.

### **Cold Water (C)**

- 70° F (26.7° C) maximum.
- A 1" minimum NPT fitting should be provided.
- Vacuum Sterilizer:
  - 30 to 50 minimum dynamic psig
  - Peak consumption is 15 GPM (130gal/hr);

### **Steam (S) (House-Steam Units only)**

- A steam trap should be installed in the line immediately upstream of the utility shutoff.
- A 1" NPT fitting should be available.
- Peak Flow 190 - 335 lbs/hour depending on model.
- 50-80 psig dynamic/static, 97 - 100% vapor quality

### **Drain (D)**

- 2" ODT drain terminal and floor drain capable of handling peak water consumption.
- The drain line must be connected to a receiver capable of withstanding 140° F water otherwise a drain cooler will be required.

### **Electricity (E)**

- Outlet box for 120 VAC, 50/60 Hz, 1 Amp (5.5 Amps for electric units) electric service to the sterilizer controls.